


22260	14in 50LB UV BLK MOUNTING TIE
--------------	--------------------------------------

UPC: 08593722260
 UNSPSC: 39121703
 Standard Qty: 100
 Master Carton Qty: 5000
 Country of Origin: HONDURAS

14" Mounting Hole Cable Tie, 50lb Tensile Strength, Black, Nylon 6/6, Plenum Rated, UV Rated, Temp Rating -40 to 185 F, Flammability Rating: UL 94-V2, Bag/100



Product Attributes		Compliance Information
Brand Name	Minerallac	Buy America Act Compliant: No
Sub Brand	Cully	Buy American Act Compliant: No
Type	Mounting Cable Tie	RoHS Compliant: Yes
Application	Mounting hole cable ties are effective for use in a wide variety of cable and wire bundling applications that require that a wire or cable bundle be attached to another surface such as a control panel, wall, or ceiling. This design allows for use of a screw or rivet for clamping.	UL Listed: No
Benefits/ Features	Designed with a special mounting hole, these cable ties are recommended when position is critical or the application requires the product be premounted to a surface before final assembly.	UL Code:
Length (in)	15.1 in	Proposition 65
Tensile Strength (lb)	50 lbs	This product is in compliance with Prop65; it is not known to contain any chemicals associated with this regulation.
Width (in)	0.18 in	
Thickness (in)	0.06 in	
Bundle Diameter	4 in	
Mounting Screw	#10	
Temperature Rating	-40 degrees F -185 degrees F	
Flammability Rating	UL 94-V2	
Material	Nylon 66	
		Minerallac Company
		Tel: 800-927-3293
		Fax: 800-824-8942
		www.minerallac.com

WARRANTY DISCLAIMER The information, data and recommendations contained herein may not be all inclusive or specific to your situation, and should only be used as a guide. The information is furnished upon the condition that the person receiving it shall make his/her own determination of the suitability of the product for his/her particular use and on condition that they assume the risk of the use thereof.

With respect to this publication and the product related thereto, except otherwise expressly provided by Manufacturer in writing, MANUFACTURER MAKES NO EXPRESS OR IMPLIED WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR ANY OTHER EXPRESS OR IMPLIED WARRANTY.

Remedy/Liability Limits The exclusive remedy for losses or damages resulting from this publication or the related product (including claims based on contract, negligence, strict liability or other legal theories) shall be limited to, at Manufacturer's sole election, one of the following: 1. Refund of purchase price paid by buyer or user for product bought, or 2. Replacement of amount of product used.

Manufacturer shall not be liable for losses or damages resulting from use of this publication or handling or use of this product, IN NO CASE SHALL MANUFACTURER BE LIABLE FOR CONSEQUENTIAL OR INCIDENTAL DAMAGES OR LOSSES, INCLUDING WITHOUT LIMIT, HEALTH RELATED DAMAGES OR INJURIES, OR LOST PROFITS.

The terms of this Warranty Disclaimer and Remedy/Liability Limits cannot be varied by any written or verbal statements or agreements. No employee or sales agent of Manufacturer or the seller is authorized to vary or exceed the terms of this Warranty Disclaimer or Limitation of Remedies in any manner.