

<b>22262</b>	<b>14in 120LB NATURAL MNTING TIE</b>
--------------	--------------------------------------

UPC: 08593722262  
 UNSPSC: 39121703  
 Standard Qty: 100  
 Master Carton Qty: 2000



Country of Origin: HONDURAS  
 14" Mounting Hole Cable Tie, 120lb Tensile Strength, Natural, Nylon 6/6, Plenum Rated, Temp Rating -40 to 185 F, Flammability Rating: UL 94-V2, Bag/100

Product Attributes		Compliance Information
Brand Name	Minerallac	Buy America Act Compliant: No
Sub Brand	Cully	Buy American Act Compliant: No
Type	Mounting Cable Tie	RoHS Compliant: Yes
Application	Mounting hole cable ties are effective for use in a wide variety of cable and wire bundling applications that require that a wire or cable bundle be attached to another surface such as a control panel, wall, or ceiling. This design allows for use of a screw or rivet for clamping.	UL Listed: No
Benefits/ Features	Designed with a special mounting hole, these cable ties are recommended when position is critical or the application requires the product be premounted to a surface before final assembly.	UL Code:
Length (in)	15.7 in	<b>Proposition 65</b>
Tensile Strength (lb)	120 lbs	This product is in compliance with Prop65; it is not known to contain any chemicals associated with this regulation.
Width (in)	0.3 in	
Thickness (in)	0.07 in	
Bundle Diameter	4 in	
Temperature Rating	-40 degrees F -185 degrees F	
Flammability Rating	UL 94-V2	
Material	Nylon 66	
		<b>Minerallac Company</b>
		Tel: 800-927-3293 Fax: 800-824-8942 www.minerallac.com

**WARRANTY DISCLAIMER** The information, data and recommendations contained herein may not be all inclusive or specific to your situation, and should only be used as a guide. The information is furnished upon the condition that the person receiving it shall make his/her own determination of the suitability of the product for his/her particular use and on condition that they assume the risk of the use thereof.

With respect to this publication and the product related thereto, except otherwise expressly provided by Manufacturer in writing, MANUFACTURER MAKES NO EXPRESS OR IMPLIED WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR ANY OTHER EXPRESS OR IMPLIED WARRANTY.

**Remedy/Liability Limits** The exclusive remedy for losses or damages resulting from this publication or the related product (including claims based on contract, negligence, strict liability or other legal theories) shall be limited to, at Manufacturer's sole election, one of the following: 1. Refund of purchase price paid by buyer or user for product bought, or 2. Replacement of amount of product used.

Manufacturer shall not be liable for losses or damages resulting from use of this publication or handling or use of this product, IN NO CASE SHALL MANUFACTURER BE LIABLE FOR CONSEQUENTIAL OR INCIDENTAL DAMAGES OR LOSSES, INCLUDING WITHOUT LIMIT, HEALTH RELATED DAMAGES OR INJURIES, OR LOST PROFITS.

The terms of this Warranty Disclaimer and Remedy/Liability Limits cannot be varied by any written or verbal statements or agreements. No employee or sales agent of Manufacturer or the seller is authorized to vary or exceed the terms of this Warranty Disclaimer or Limitation of Remedies in any manner.