

60404SSJ	3/8-16 DROP-IN ANCHOR 304SS
-----------------	------------------------------------

UPC: 08593703975
 UNSPSC: 31161601
 Standard Qty: 100
 Master Carton Qty: 600
 Country of Origin: CHINA
 3/8" - 16 Drop-In Anchor, Drill Bit Dia. 1/2", Anchor Length 1-5/8", Type 304 Stainless Steel, Jar



Product Attributes		Compliance Information
Brand Name	Minerallac	Buy America Act Compliant: No
Sub Brand	Cully	Buy American Act Compliant: No
Type	Steel Drop-In Anchor	RoHS Compliant: Yes
Size	3/8"-16 x 1-9/16"	UL Listed: No
Diameter	0.375"	UL Code:
Length	1.563"	Proposition 65
Minimum Embedment Depth	1.625"	This product is in compliance with Prop65; it is not known to contain any chemicals associated with this regulation.
Thread Type	Internal Threads	Minerallac Company
Thread per Inch	16	Tel: 800-927-3293
Drill Size	1/2"	Fax: 800-824-8942
Material	Steel	www.minerallac.com
Finish	Zinc Plated	
Shear Strength	1138lbs in 2000psi normal weight concrete. 3160lbs in 4000 psi normal weight concrete	
Thread Length	0.625"	
Ultimate Tension Strength	538lbs in 2000psi normal weight concrete. 2000lbs in 4000psi normal weight concrete	

WARRANTY DISCLAIMER The information, data and recommendations contained herein may not be all inclusive or specific to your situation, and should only be used as a guide. The information is furnished upon the condition that the person receiving it shall make his/her own determination of the suitability of the product for his/her particular use and on condition that they assume the risk of the use thereof.

With respect to this publication and the product related thereto, except otherwise expressly provided by Manufacturer in writing, MANUFACTURER MAKES NO EXPRESS OR IMPLIED WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR ANY OTHER EXPRESS OR IMPLIED WARRANTY.

Remedy/Liability Limits The exclusive remedy for losses or damages resulting from this publication or the related product (including claims based on contract, negligence, strict liability or other legal theories) shall be limited to, at Manufacturer's sole election, one of the following: 1. Refund of purchase price paid by buyer or user for product bought, or 2. Replacement of amount of product used.

Manufacturer shall not be liable for losses or damages resulting from use of this publication or handling or use of this product, IN NO CASE SHALL MANUFACTURER BE LIABLE FOR CONSEQUENTIAL OR INCIDENTAL DAMAGES OR LOSSES, INCLUDING WITHOUT LIMIT, HEALTH RELATED DAMAGES OR INJURIES, OR LOST PROFITS.

The terms of this Warranty Disclaimer and Remedy/Liability Limits cannot be varied by any written or verbal statements or agreements. No employee or sales agent of Manufacturer or the seller is authorized to vary or exceed the terms of this Warranty Disclaimer or Limitation of Remedies in any manner.