

<b>60404USJ</b>	<b>3/8-16 STEEL DROP-IN ANCHOR</b>
-----------------	------------------------------------

UPC: 08593705804  
 UNSPSC: 31162101  
 Standard Qty: 100  
 Master Carton Qty: 600  
 Country of Origin: USA  
 3/8"-16 x 1-9/16" Steel Drop-In Anchors, Includes Setting Tool, Zinc Plated, 100/Jar



Product Attributes		Compliance Information
Brand Name	Minerallac	Buy America Act Compliant: Yes
Sub Brand	Cully	Buy American Act Compliant: Yes
Type	Steel Drop-In Anchor	RoHS Compliant: Yes
Application	Steel Drop-In Anchor is an all steel anchor for use in solid concrete, lightweight concrete, and concrete-filled steel deck members. The anchors can also be considered for hand stone and solid block base materials.	UL Listed: No
Uses	Suspending conduit, concrete formwork, fire sprinkler supports, pipe supports, cable trays and strut, suspended lighting	UL Code:
Material	Carbon Steel	<b>Proposition 65</b>
Overall Length	1-9/16"	This product is in compliance with Prop65; it is not known to contain any chemicals associated with this regulation.
Outside Diameter	1/2"	
Minimum Embedment Depth	1-9/16"	
Rod/ Anchor Size	3/8"	
Ultimate Load Capacities (2000 PSI Concrete)	2180 lbs Tension, 4585 lbs Shear	
Allowable Load Capacities (2000 PSI Concrete)	545 lbs Tension, 1145 lbs Shear	
		<b>Minerallac Company</b>
		Tel: 800-927-3293 Fax: 800-824-8942 www.minerallac.com

**WARRANTY DISCLAIMER** The information, data and recommendations contained herein may not be all inclusive or specific to your situation, and should only be used as a guide. The information is furnished upon the condition that the person receiving it shall make his/her own determination of the suitability of the product for his/her particular use and on condition that they assume the risk of the use thereof.

With respect to this publication and the product related thereto, except otherwise expressly provided by Manufacturer in writing, MANUFACTURER MAKES NO EXPRESS OR IMPLIED WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR ANY OTHER EXPRESS OR IMPLIED WARRANTY.

**Remedy/Liability Limits** The exclusive remedy for losses or damages resulting from this publication or the related product (including claims based on contract, negligence, strict liability or other legal theories) shall be limited to, at Manufacturer's sole election, one of the following: 1. Refund of purchase price paid by buyer or user for product bought, or 2. Replacement of amount of product used.

Manufacturer shall not be liable for losses or damages resulting from use of this publication or handling or use of this product, IN NO CASE SHALL MANUFACTURER BE LIABLE FOR CONSEQUENTIAL OR INCIDENTAL DAMAGES OR LOSSES, INCLUDING WITHOUT LIMIT, HEALTH RELATED DAMAGES OR INJURIES, OR LOST PROFITS.

The terms of this Warranty Disclaimer and Remedy/Liability Limits cannot be varied by any written or verbal statements or agreements. No employee or sales agent of Manufacturer or the seller is authorized to vary or exceed the terms of this Warranty Disclaimer or Limitation of Remedies in any manner.