

60405	3/8-16 SHALLOW EMBEDMENT DROP
--------------	--------------------------------------

UPC: 08593760405
 UNSPSC: 31162101
 Standard Qty: 100
 Master Carton Qty: 1000
 Country of Origin: CHINA
 3/8-16" Shallow Embedment Steel Drop-In Anchor, Includes Setting Tool, Zinc Plated



Product Attributes		Compliance Information	
Brand Name	Minerallac	Buy America Act Compliant: No	
Sub Brand	Cully	Buy American Act Compliant: No	
Type	Mini Dropin expansion anchor	RoHS Compliant: Yes	
Application	A carbon steel machine bolt anchor designed for use in shallow embedment applications.	UL Listed: No	
Material	Zinc Plated Carbon Steel	UL Code:	
Suitable Base Materials	Normal Weight Concrete, Lightweight Concrete, Precast Hollow Core Plank, and Concrete Over Steel Deck	Proposition 65	
Benefits/ Features	Internally threaded anchor for easy bolt removability and service work, ideal for precast hollow core plank and post-tensioned concrete slabs, lip provides flush installation and consistent embedment, Manual setting tool scores flange when set to verify proper expansion depth	This product is in compliance with Prop65; it is not known to contain any chemicals associated with this regulation.	
Rod/ Anchor Diameter	3/8"	Minerallac Company	
Outside Diameter	1/2"		
Overall Length	3/4"		
Minimum Embedment Depth in.	3/4"		
Ultimate Tension Strength (3,000 PSI)	1,980 lbs		
Ultimate Shear Strength (3,000 PSI)	2,700 lbs		
Allowable Tension Strength (3,000 PSI)	495 lbs		
Allowable Shear Strength (3,000 PSI)	675 lbs		
			Tel: 800-927-3293
			Fax: 800-824-8942
		www.minerallac.com	

60405

3/8-16 SHALLOW EMBEDMENT DROP

UPC: 08593760405

UNSPSC: 31162101

Standard Qty: 100

Master Carton Qty: 1000

Country of Origin: CHINA

3/8-16" Shallow Embedment Steel Drop-In Anchor, Includes Setting Tool, Zinc Plated



WARRANTY DISCLAIMER The information, data and recommendations contained herein may not be all inclusive or specific to your situation, and should only be used as a guide. The information is furnished upon the condition that the person receiving it shall make his/her own determination of the suitability of the product for his/her particular use and on condition that they assume the risk of the use thereof.

With respect to this publication and the product related thereto, except otherwise expressly provided by Manufacturer in writing, MANUFACTURER MAKES NO EXPRESS OR IMPLIED WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR ANY OTHER EXPRESS OR IMPLIED WARRANTY.

Remedy/Liability Limits The exclusive remedy for losses or damages resulting from this publication or the related product (including claims based on contract, negligence, strict liability or other legal theories) shall be limited to, at Manufacturer's sole election, one of the following: 1. Refund of purchase price paid by buyer or user for product bought, or 2. Replacement of amount of product used.

Manufacturer shall not be liable for losses or damages resulting from use of this publication or handling or use of this product, IN NO CASE SHALL MANUFACTURER BE LIABLE FOR CONSEQUENTIAL OR INCIDENTAL DAMAGES OR LOSSES, INCLUDING WITHOUT LIMIT, HEALTH RELATED DAMAGES OR INJURIES, OR LOST PROFITS.

The terms of this Warranty Disclaimer and Remedy/Liability Limits cannot be varied by any written or verbal statements or agreements. No employee or sales agent of Manufacturer or the seller is authorized to vary or exceed the terms of this Warranty Disclaimer or Limitation of Remedies in any manner.