

60406USJ	1/2-13 STEEL DROP-IN ANCHOR
-----------------	------------------------------------

UPC: 08593705808
 UNSPSC: 31161601
 Standard Qty: 50
 Master Carton Qty: 300
 Country of Origin: USA
 1/2"-13 x 2" Steel Drop-In Anchors, Includes Setting Tool, Zinc Plated, 50/Jar



Product Attributes		Compliance Information
--------------------	--	------------------------

Brand Name	Minerallac
Sub Brand	Cully
Type	Steel Drop-In Anchor
Application	Steel Drop-In Anchor is an all steel anchor for use in solid concrete, lightweight concrete, and concrete-filled steel deck members. The anchors can also be considered for hand stone and solid block base materials.
Uses	Suspending conduit, concrete formwork, fire sprinkler supports, pipe supports, cable trays and strut, suspended lighting
Material	Carbon Steel
Overall Length	2"
Outside Diameter	5/8"
Minimum Embedment Depth	2"
Rod/ Anchor Size	1/2"
Ultimate Load Capacities (2000 PSI Concrete)	4,105 lbs Tension, 6,400 lbs Shear
Allowable Load Capacities (2000 PSI Concrete)	1,025 lbs Tension, 1,600 lbs Shear

Buy America Act Compliant:	Yes
Buy American Act Compliant:	Yes
RoHS Compliant:	Yes
UL Listed:	No
UL Code:	
Proposition 65	
This product is in compliance with Prop65; it is not known to contain any chemicals associated with this regulation.	

Minerallac Company
Tel: 800-927-3293 Fax: 800-824-8942 www.minerallac.com

WARRANTY DISCLAIMER The information, data and recommendations contained herein may not be all inclusive or specific to your situation, and should only be used as a guide. The information is furnished upon the condition that the person receiving it shall make his/her own determination of the suitability of the product for his/her particular use and on condition that they assume the risk of the use thereof.

With respect to this publication and the product related thereto, except otherwise expressly provided by Manufacturer in writing, MANUFACTURER MAKES NO EXPRESS OR IMPLIED WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR ANY OTHER EXPRESS OR IMPLIED WARRANTY.

Remedy/Liability Limits The exclusive remedy for losses or damages resulting from this publication or the related product (including claims based on contract, negligence, strict liability or other legal theories) shall be limited to, at Manufacturer's sole election, one of the following: 1. Refund of purchase price paid by buyer or user for product bought, or 2. Replacement of amount of product used.

Manufacturer shall not be liable for losses or damages resulting from use of this publication or handling or use of this product, IN NO CASE SHALL MANUFACTURER BE LIABLE FOR CONSEQUENTIAL OR INCIDENTAL DAMAGES OR LOSSES, INCLUDING WITHOUT LIMIT, HEALTH RELATED DAMAGES OR INJURIES, OR LOST PROFITS.

The terms of this Warranty Disclaimer and Remedy/Liability Limits cannot be varied by any written or verbal statements or agreements. No employee or sales agent of Manufacturer or the seller is authorized to vary or exceed the terms of this Warranty Disclaimer or Limitation of Remedies in any manner.