

<b>61204J</b>	<b>SAMMY SXP35 SWIVEL X-PRESS</b>
---------------	-----------------------------------

UPC: 08593799690  
 UNSPSC: 31161502  
 Standard Qty: 25  
 Master Carton Qty: 150  
 Country of Origin: USA  
 ITW Sammys® SXP 35 SWIVEL X-PRESS for 22g.-0.125" Purlin, 89° Max Swivel Mounting, 3/8" Rod, Model #SXP 35, Zinc Plated, 25ct Jar



Product Attributes		Compliance Information
Brand Name	Minerallac	Buy America Act Compliant: No
Sub Brand	Cully	Buy American Act Compliant: No
Type	Rod Anchor	RoHS Compliant: Yes
Special Features	Installs in seconds, saving time & installation costs. Swivel head allows for anchoring to the metal decking at an adjustable angle.	UL Listed: No
Application	Use in applications where access to the back of the installed fastener is prohibited. ie. metal roof deck, tubular steel, or vapor barrier fabric. No retaining nut required.	UL Code:
Material	Steel	<b>Proposition 65</b>
Rod Size	3/8"	This product is in compliance with Prop65; it is not known to contain any chemicals associated with this regulation.
Head Color	Silver	
Finish	Electro-Zinc	
Type	SXP 35 SWIVEL X-PRESS Sammy's threaded rod anchor for Purlin 3/8" rod	
Special Features	One-step installation process reduces installation time and cost.	
Application	Use in applications where access to the back of the installed fastener is prohibited, ie. Metal roof deck, tubular steel, or vapor barrier fabric	
Substrate	Metal Deck	
Mounting	Swivel	
Max Swivel Degrees	89°	
Ultimate Pullout (lbs)	1675 (16 ga Vert) 1558 (89° Off Vert)	

## Minerallac Company

Tel: 800-927-3293  
 Fax: 800-824-8942  
[www.minerallac.com](http://www.minerallac.com)

**WARRANTY DISCLAIMER** The information, data and recommendations contained herein may not be all inclusive or specific to your situation, and should only be used as a guide. The information is furnished upon the condition that the person receiving it shall make his/her own determination of the suitability of the product for his/her particular use and on condition that they assume the risk of the use thereof.

With respect to this publication and the product related thereto, except otherwise expressly provided by Manufacturer in writing, MANUFACTURER MAKES NO EXPRESS OR IMPLIED WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR ANY OTHER EXPRESS OR IMPLIED WARRANTY.

**Remedy/Liability Limits** The exclusive remedy for losses or damages resulting from this publication or the related product (including claims based on contract, negligence, strict liability or other legal theories) shall be limited to, at Manufacturer's sole election, one of the following: 1. Refund of purchase price paid by buyer or user for product bought, or 2. Replacement of amount of product used.

Manufacturer shall not be liable for losses or damages resulting from use of this publication or handling or use of this product, IN NO CASE SHALL MANUFACTURER BE LIABLE FOR CONSEQUENTIAL OR INCIDENTAL DAMAGES OR LOSSES, INCLUDING WITHOUT LIMIT, HEALTH RELATED DAMAGES OR INJURIES, OR LOST PROFITS.

The terms of this Warranty Disclaimer and Remedy/Liability Limits cannot be varied by any written or verbal statements or agreements. No employee or sales agent of Manufacturer or the seller is authorized to vary or exceed the terms of this Warranty Disclaimer or Limitation of Remedies in any manner.